



REV.	REVISION	BY	DATE
C	NOTCHES IN HEAD REMOVED DIMENSIONING COMPLETED MATL WAS SAE 3135	KRUG	9-16-42
D	WAR MATL SUBSTITUTION (PART NO. 8060883, 8068727, 8068763 8070364) REMOVED	MARTIN FOX B	1-5-43
E	ei LOCATION OF DIMENSION CORRECTED	Carey	6-6-44
F	R.F.C. No. WAS "NE 8339 C-0894 STEEL"	CROW	3-1-46
G	U2067 HEAT TREAT NOTE REMOVED MATL. WAS SAE 3140 STL. G, WAS .384 -- .365	Baker	3-21-57
H	A 4937 MATL WAS GM-290M	W.D.D.	2-3-64
J	29239 I WAS 3-20 NE CL3 I.I. & DIM. REMOVED TR DIM ADDED JEMRG ADDED	W.D.D.	10-20-64

TOLERANCE ON FRACTIONAL DIMENSIONS
UNLESS OTHERWISE SPECIFIED

CASTINGS & FORGINGS

FABRICATION

MACHINING $\pm .005$

⑦ MATERIAL:

ELECTRO-MOTIVE DIVISION

GENERAL MOTORS CORPORATION

LA GRANGE, ILLINOIS, U.S.A.

BOLT-1/2-20 DR HEX
567

MADE BY
ROSEN

DATE
7-14-37

DR
NO

802829

DATE OF PRINT

REVISION





