

TS 12708 Steel Casting		
<1000	6,0	0,8
<630	4,0	0,7
<400	3,0	0,6
<250	3,0	0,4
100	2,0	0,3
40	1,5	0,2
L mm	Raw	Form
Nom. Size	Class	

ISO 2768 General Tolerance		
<4000	2,0	0,4
<2000	1,2	0,4
<1000	0,8	0,3
<400	0,5	0,3
30-120	0,3	0,2
2-30	0,2	0,1
L mm	m ±	K ±
Nom. Size	Class	

ISO 13920 Welded Construction		
>20000	9,0	8,0
<20000	8,0	7,0
<16000	7,0	6,0
<12000	6,0	5,0
<8000	5,0	4,0
<4000	4,0	3,0
<2000	3,0	2,0
<1000	2,0	1,5
<400	1,0	1,0
30-120	1,0	0,5
2-30	1,0	0,5
L mm	A ±	E ±
Nom. Size	Class	

Technical Specifications	-				
Technical Document	-				
Fixture/Mould Asset ID.	-				
Coating/Heat Tre./Roughness	-				
Paint/Color	-	Modf.No	Modification Description	Date	Sign

No	Parça Adý Designation Name of Item	Adet Qty.	Resim No / Norm Drawing No / Norm	Malzeme Material	Ölçü Dimension	Ağirlik Weight (Kg)
TYP						

ISO 1302 ISO 8015 EN 22553			General Tol.	ISO 2768	f ☐ m☒ H☐ K☒
EN 15085-2 Certification Level	CL1 ☒ CL2 ☐ CL3 ☐ CL4 ☐		Weld Prod.	ISO 13920	A☒ B☐ E☒ F☐
			Cast Steel	ISO 12708	Lm2☐ Lr2☐ Sm2☐ Sr2☐
Approved	P.FARINA		Scale		
Checked	M.BORLO		1:2		
Prepared	D.CARLINO				

Cable DRUSE IDT L=570

TÜVASAS
Turkish Wagon Industry

EM20.24.11.20002

Date:08/05/2019 | Sheet:1/1 | Size:A3 | Rev:00

Reproduction, dissemination or use of this document or its all contents in any form without the prior written permission of TUVASAS, is prohibited. Offenders will be liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or ornamental design registration.