



Flat countersunk head with cross recess

L/d	2,2	2,9	3,5	3,9	4,2	4,8	5,5	6,3
4,5	001	006						
6,5	002	007	016	027				
9,5	003	008	017	028	038	048		
13	004	009	018	029	039	049	062	076
16	005	010	019	030	040	050	063	077
19		011	020	031	041	051	064	078
22		012	021	032	042	052	065	079
25		013	022	033	043	053	066	080
32		014	023	034	044	054	067	081
38		015	024	035	045	055	068	082
45			025	036	046	056	069	083
50			026	037	047	057	070	084
60						058	071	085
70						059	072	086
80						060	073	087
90						061	074	
100							075	

D	4,3	5,5	6,8	7,5	8,1	9,5	10,8	12,4
K	1,3	1,7	2,1	2,3	2,5	3	3,4	3,8

To create the complete part number for normalized item refer to the following table

	TUVASAS Standard							
	Fix	.	Main Group	Subgroup	-	Dash Number	Materia *	Treatment*
Generic	SP	.	XX	XXX	-	XXX	X	X
Example	SP	.	01	001	-	111	J	B

\* For material and treatment refer to standard SP.00.001

Standard Reference	ISO 7050	Issue Date	27/09/2018
TUVASAS Standard	SP.01015	Rev. Date	27/09/2018
Flat countersunk head with cross recess	Rev. 00	Sheet	1 Of 1
-	-	-	-

All rights reserved. No parts of this document may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and micro film without permission in write form.