8024846

PERMISSIBLE VARIATION ON COMMON FRACTION DIMENSIONS TO MACHINED SURFACES TO BE ±1/64 UNLESS OTHERWISE SPECIFIED. ±.005

BREAK ALL SHARP CORNERS UNLESS OTHERWISE SPECIFIED.

COUNTERSINK ALL TAPPED HOLES 118° & ONE DIA'D DEEP

APERTURE CARD ONLY

2 Adet ϕ 5,159 delik



(M) CARBURIZE FOR .005-.010
(P) CASE DEPTH.
QUENCH IN WATER.
TEMPER AT 350°F.
ROCKWELL "15N" 88 MIN.
(TIP ONLY)

FINISH ALL OVER

Yer No	Sira No
1710	415

S.F.C. NO.	REV. LET.	REVISION	DATE	BY	CK.	APP'D
A10953	R, R	PD REMOVED WAS 32-10 NF CL 3	12 JAN 60	A.R.		

S.F.C. NO.	REV. LET.	REVISIONS	DATE	BY	CK.	APP'D
Y-3279	P	HEAT TREAT REVISED	12-5-41	M.G.		
X-1033	N	WAS 5/8" N.-W.S. 6 23/32"	6-15-40			
		NOTE WD. "CYANIDE				
		HARDEN TIP ONLY"				
E-7480	M	REDRAWN	5-1-40			
		SHEET USED ON 2569				

MATERIAL: S.A.E. 1112 STEEL

DR.	MCKENSON	2-14-38
CH.	WELLMAN	2-18-38
ENG.		
APP'D		
MGR.		

NAME OF PART: NEEDLE VALVE - CYL TEST

PART NO.

ELECTRO-MOTIVE DIVISION
GENERAL MOTORS CORPORATION
LA GRANGE, ILLINOIS, U.S.A.

SIZE OF PRINT: B

PART NO. 8024846

B